



Boost Storage Performance Using Intel® Optane™ SSDs and Intel® QLC 3D NAND SSDs

Boost storage performance using Intel® Optane™ technology and Intel® QLC 3D NAND SSDs with Intel® Cache Acceleration Software.

Challenge: Applications require fast and responsive storage systems at a low cost

Storage applications are responsible for servicing millions of requests every day. Many enterprise storage solutions are run on hard-disk drive media. In order to meet high-speed application needs, many users have migrated to TLC SSD back-end infrastructures for added performance boosts. For others, a more economical alternative is preferred. In response, Intel introduces a unique solution implementing Intel® SSD D5-P4320 + QLC, Intel® Optane™ SSD DC P4800X, and Intel® Cache Acceleration Software (Intel® CAS) to increase storage application performance in a cost-effective manner.

Solution: Intel® Optane™ Technology and QLC deliver up to 1.9x increase in IOPS¹

In this reference solution an I/O workload was generated using the FIO tool with a 70:30 read/write ratio, 4KB block size, and random reads/writes. Under this workload, the Intel® Optane™ SSD DC P4800X caching for a back-end Intel® Virtual RAID on CPU (Intel® VROC) RAID5 array of SSD D5-P4320 + QLC yielded a 1.9x increase in IOPS performance along with a 3.1x decrease in average latency relative to a TLC configuration composed of Intel® SSD DC P4510 + TLC in an Intel VROC RAID5 array.¹ Additionally, these improvements were attained at a reduced economic price point.² This enables storage solution deployment at lower cost and higher performance with an Intel® Optane™ technology-driven solution.¹




Figure 1: IOPS and latency improvements for Intel® Optane™ Technology + Intel® QLC 3D NAND SSDs vs. TLC

Conclusion

This reference solution utilizing Intel® QLC 3D NAND SSDs, Intel® Optane™ Technology and Intel® CAS allows users to unleash the higher performance and predictable latency of Intel® Optane™ Technology while leveraging the cost-effectiveness of Intel® QLC 3D NAND SSDs.



Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit [intel.com/benchmarks](https://www.intel.com/benchmarks).

1. System configuration: Server model: Intel® Wolf Pass S2600WFT (R2208WFTZS); MB: H48104-710; CPU: Dual Intel(R) Xeon(R) Platinum 8160T CPU @ 2.10GHz, 24C/48T, 10.4GT/s, 33 MB L3 Cache, Turbo, HT (150W) DDR4-2666; Mem: 4x32GB RDIMM (128GB), 2400MT/s, DDR4-19200; NICs: Intel® 10-Gigabit x540-AT2 (Rev. 01) and Embedded Intel® X722 10GbE LAN; TLC config: 4x Intel® SSD DC P4510 8TB in VROC RAID5 for capacity storage; QLC config: 4x Intel® SSD DC P4320 8TB in VROC RAID5 for capacity storage and 1x Intel® Optane SSD DC P4800X 375GB for caching; Workload: FIO, size=760G, 3000 files (individual filesize ~ 256MB), test block size 4kb, time-based two-hour sequential write conditioning (block size 128kb), time-based 20-min test (20-min runtime, 30-second ramp time), zipf random distribution (theta = 1.1). TLC system obtained 82,648 IOPs and 185.74 µs latency on average. QLC system obtained 153,795 IOPs and 60.04 µs on average. Performance results are based on testing as of July 19, 2018 and may not reflect the publicly available security updates. See configuration disclosure for details. No product can be absolutely secure.

2. Cost reduction based on \$0.37/GB for TLC SSDs, \$0.29/GB for QLC SSDs, \$2.87/GB for Intel® Optane™ SSDs. Total TLC capacity 4x8000GB. Total QLC capacity 4x7680GB. Total Intel Optane SSD capacity 1x375GB. Sources: <https://www.cdw.com/product/intel-solid-state-drive-dc-p4510-series-solid-state-drive-8-tb-pci-ex/5101252>; <https://colfaxdirect.com/store/pc/viewPrd.asp?idproduct=3223&idcategory=0>; <https://www.cdw.com/product/intel-solid-state-drive-d5-p4320-series-solid-state-drive-7.6-tb-pci/5400292?enkwrd=p4320>

Optimization Notice: Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice. Notice Revision #20110804.

Intel technologies may require enabled hardware, specific software, or services activation. Check with your system manufacturer or retailer.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software, or service activation. Performance varies depending on system configuration. No product or component can be absolutely secure. Check with your system manufacturer or retailer, or learn more at [intel.com](https://www.intel.com).

Intel, the Intel logo, and Intel Optane are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

*Other names and brands may be claimed as the property of others.